## MATERIAL SAFETY DATA SHEET

			ATERIAL SAI	ETY	DATA SH	EET				
SECTION 1 - PROI	OUCT IDENTIFICA	ATION ANI	O USE							
PRODUCT IDENTIFIER:	ZE 1145 TEXTURE AUTUMN			PRODUCT IDENTIFICATION NUMBER 1145						
PRODUCT USE : CERAMIC	GLAZE			1						
MANUFACTURER'S NAME	E SPECTRUM G	LAZES I	NC. SUPPLIER'S NAME			S NAME	SPECTRUM GLAZES INC.			
STREET ADDRESS: 273	BOWES RD, U	NIT A1	STREET			T ADDRESS: 273 BOWES RD, UNIT A1				
CITY: CONCORD	: ONTAR	IO CITY: CO			NCORD	PROV	/INCE	: ONTARIO		
POSTAL CODE: L4K1H8	EL(905)	695-8355	95-8355 POSTAL CODE: L4F			1H8 EMERGEN	ICY T	EL(905)695-8355		
SECTION 2 - HAZARDOUS	S INGREDIENTS									
HAZARDOUS INGREDIENTS		olo	CAS NUMBI		LD50 OF INGREDIENTS (SPECIFY SPECIES AND ROUTE)			E)	LC50 OF INGREDIENT (SPECIFY SPECIES)	
Si02		20-35	14808-60-7		ILV 15mg/m3 OSHA/TWA					
K20		1-3	12136-45-7							
CaO		15-20	1305-78	8-8						
Na2O		1-3	1313-59	9-3						
A1203		13-16	1344-28	8-1						
B203		3-4	1303-86	5-2						
ZnO		10-12	1314-13	3-2						
CERAMIC STAIN - CORAL		2-3	68186-1	3-3						
SECTION 3 - PHYSICAL	DATA									
PHYSICAL STATE LIQUID	ODOUR AND APPEARANCE ODOUR THRESHOLD(PPM) ODOURLESS LIQUID N.A.								, ,	
VAPOUR PRESSURE (mm Hg) N.A.	VAPOUR DENSI	EVAPORATION RATE N.A.			BOILING POINT(C) N.A.		FREEZING POINT(C) N.A.			
рн 6.5-7	SPECIFIC GRAVITY COEFF. WA			TER/OIL DIST.						
SECTION 4 - FIRE F	AND EXPLOSION I	DATA	<u> </u>					1		
FLAMMABILITY YES NO	X FLAMES U	NDER WHI	CH CONDITIO	ONS :	THIS P	RODUCT DO	DES NOT SUPP	ORT C	OMBUSTION	
MEANS OF EXTINCTION N	O SPECIAL MEAN	IS REQUIR	ED				Т			
FLASHPOINT AND METHOD		UPPER FLAMMABLE LIMIT (% BY VOLUME) N.A.  LOWER FLAMMABLE L (% BY VOLUME) N.A.								
AUTOIGNITION TEMP.(C)		HAZARDOUS COMBUSTION PRODUCTS NONE								
EXPLOSION DATA N.A.	SENSITIVITY	IMPACT N	.A.	AC	TIVITY	TO STATIO	C DISCHARGE	N.A.		
		SI	ECTION 5 -	REACI	I YTIVI	ATA				
CHEMICAL STABILITY YES X NO IF NO,	UNDER WHICH C	CONDITION	īS							
INCOMPATIBILITY WITH YES NO X IF SO										
REACTIVITY AND UNDER			ACTIVITY							

HAZARDONE DECOMPOSTBYON DESCRICE. MARRETAL TO CHARTE NO DOLYMENTZABYON DUB BOYTO BIMES MAY BE DELEASED MIEN.

PRODUCT IDENTIFIER SPECTRUM LEAD FREE 1145 TEXTURE AUTUMN										
SECTION 6 - TOXICOLOGICAL PROPERTIES										
ROUTE OF ENTRY SKIN CONTACT	SK	IN ABSORPTION X	EYE CONTACT X I	NHALATION	INGESTION X					
EFFECTS OF ACUTE EXPOSURE TO PRODUCT: SKIN IRRITATION DUE TO ABRASIVENESS.  EYE EXPOSURE COULD CAUSE IRRITATION BUT NO TOXIC EFFECTS.										
EFFECTS OF CHRONIC EXPOSURE TO PRODUCT: METAL FUMES IN THE VAPOURS FROM FIRING CERAMIC GLAZES MAY CAUSE LUNG INFLAMATION AND DAMAGE TO KIDNEY AND NERVOUS SYSTEM.										
EXPOSURE LIMITS	IRRITANC	Y OF PRODUCT	SENSITIZATION TO F	PRODUCT	CARCINOGENICITY					
TERATOGENCITY	REPRODUC	TIVE TOXICITY	MUTAGENICITY		SYNERGISTIC PRODUCTS					
SECTION 7 - PREVENTIVE MEASURES										
PERSONAL PROTECTIVE EQUIPMENT:										
GLOVES (SPECIFY) WORK GLOVES		RESPIRATOR (SPECIAL APPROVED DUST MASK	,	EYE (SPECIFY) SAFETY GLASSES						
FOOTWEAR (SPECIFY)		CLOTHING (SPECIFY)	)	OTHER (SPECIFY)						
ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS) VENTILATION SHOULD BE USED WHEN SPRAYING GLAZES.										
LEAK AND SPILL PROCEDURE: SCOOP INTO SUITABLE RECEPTACLE. DO NOT WASH DOWN DRAIN.										
WASTE DISPOSAL: SEND TO APPROVED SITE IN ACCORDANCE WITH REGULATIONS.										
HANDLING PROCEDURES AND EQUIPMENT: NO SPECIAL EQUIPEMENT NEEDED. FOLLOW STANDARD PLANT HYGIENE PROCEDURE.										
STORAGE REQUIREMENTS: STORE IN DRY AREAS.										
SPECIAL SHIPPING INFORMATION: PROTECT AGAINST PHYSICAL DAMAGE. DOT LABEL NON-REGULATED										
SECTION 8 - FIRST AID MEASURES										
SPECIFIC MEASURES: GLAZE CONTAINS THE OXIDES LISTED IN THE CHEMICAL FORMULA IN FORM OF CERAMIC FRIT. SOME OF THESE OXIDES ARE OXIDES ARE FUSED AND CONVERTED INTO FRIT THEY ARE NO LONGER AVAILABLE IN TOXIC FORM EVEN THOUGH TESTING WOULD DETECT THE PRESENCE OF THESE OXIDES. (FRIT IS ESSENTIALLY AN INSOLUBLE SUBSTANCE). THE OXIDES ARE PRESENT IN THE FORM OF A SINTERED CERAMIC STAIN OF LOW SOLUBILITY. THESE INGREDIENTS ARE PRESENT IN A STABLE AQUEOUS SUSPENSION.										
SECTION 9 - PREPARATION DATE OF MSDS										
PREPARED BY (GROUP, DEPARTMENT, ETC.) TECHNICAL DEPT.		PHONE NUMBER: (905) 695-8355		DATE 15 OCTOBER 2015						