MATERIAL SAFETY DATA SHEET

PRODUCT IDENTIFIER : SPECTRUM LEAD FREE MENDING				PAST	PASTE PRODU		PRODUCT ID	UCT IDENTIFICATION NO. 1074	
PRODUCT USE : CERAN	MIC MENDING P	ASTE							
MANUFACTURER'S NAMI	E SPECTRUM G	LAZES IN	NC.	SUP	PLIER'	S NAME	SPECTRUM G	LAZES INC.	
STREET ADDRESS: 273 BOWES RD, UNIT A1			STREET ADDRESS: 27			DRESS: 2	73 BOWES R	D, UNIT A1	
CITY: CONCORD PROVINCE: ONTAR			CO CITY: CONCORD PROVINCE: ONTARIO			INCE: ONTARIO			
POSTAL CODE: L4K1H8 EMERGENCY TEL(905)		EL(905)6	695-8355 POSTAL CODE: L4K1		H8 EMERGEN	CY TEL(905)695-8355			
SECTION 2 - HAZARDO	OUS INGREDIEN	TS							
HAZARDOUS INGREDIENTS		00			50 OF INGREDIENTS ECIFY SPECIES AND)		LC50 OF INGREDIENT (SPECIFY SPECIES		
SiO2		30-40	14808-6	0-7	ILV 1	5mg/m3 I	TLV/TWA		
CaO		1-2	1305-78-8						
Na2O		8-12	1313-59-3						
A1203	 1203		1344-28-1						
B203		1-2	1303-86	-2					
SECTION 3 - PHYSICA	AL DATA							<u> </u>	
PHYSICAL STATE LIQUID		ODOUR AND APPEARANCE ODOUR THRESHOLD (PPEODOURLESS LIQUID N.A.					ODOUR THRESHOLD (PPM		
VAPOUR PRESSURE (mm Hg) N.A.	VAPOUR DENS (AIR=1)	ITY	EVAPORAT	RATE	ATE BOILING POINT(C) N.A.		FREEZING POINT(C)		
рн 6.5-7	SPECIFIC GRAVITY COEFF. W. 1.8-2.2 N.A.			ATER/OIL DIST.					
SECTION 4 - FIRE A	AND EXPLOSION	DATA	•						
FLAMMABILITY YES	NO X FLAM	ES UNDEF	R WHICH CO	NDIT	IONS :	THIS PR	ODUCT DOES	NOT SUPPORT	
MEANS OF EXTINCTION	N NO SPECIAL	MEANS RE	EQUIRED						
FLASHPOINT AND METHOD NONE			UPPER FLAMMABLE LIMIT (% BY VOLUME) N.A.			IT	LOWER FLAMMABLE LIMIT (% BY VOLUME) N.A.		
AUTOIGNITION TEMP.(C) N.A.			HAZARDOUS COMBUSTION PRODUCTS NONE						
EXPLOSION DATA N.A	. SENSITIV	ITY IMPA	ACT N.A.	AC'	TIVITY	TO STAT	IC DISCHAR	GE N.A.	
		SEC	TION 5 - F	REACT	'IVITY	DATA			
CHEMICAL STABILITY	NO, UNDER WHI	CH CONDI	ITIONS						
YES X NO IF I									
YES X NO IF I INCOMPATIBILITY WIT YES NO X IF S			ΙΤΥ						

MATERIAL IS MELTED.

RELEASED WHEN

PRODUCT IDENTIFIER SPECTRUM LEAD FREE 1074 MENDING PASTE

SECTION 6 - TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY

SKIN CONTACT SKIN ABSORPTION X EYE CONTACT X INHALATION

EFFECTS OF ACUTE EXPOSURE TO PRODUCT: SKIN IRRITATION DUE TO ABRASIVENESS.

EYE EXPOSURE COULD CAUSE IRRITATION BUT NO TOXIC EFFECTS.

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT: METAL FUMES IN THE VAPOURS FROM FIRING CERAMIC GLAZES MAY CAUSE LUNG

SYSTEM.

INFLAMATION AND DAMAGE TO KIDNEY AND NERVOUS SYSTEM.

EXPOSURE LIMITS	IRRITANCY OF PRODUCT	SENSITIZATION TO PRODUCT	CARCINOGENICITY
TERATOGENCITY	REPRODUCTIVE TOXICITY	MUTAGENICITY	SYNERGISTIC PRODUCTS

SECTION 7 - PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT:

INGESTION X

GLOVES (SPECIFY)	RESPIRATOR (SPECIFY)	EYE (SPECIFY)
WORK GLOVES	APPROVED DUST MASK	SAFETY GLASSES
FOOTWEAR (SPECIFY)	CLOTHING (SPECIFY)	OTHER (SPECIFY)

ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS) VENTILATION SHOULD BE USED WHEN SPRAYING GLAZES.

LEAK AND SPILL PROCEDURE: SCOOP INTO SUITABLE RECEPTACLE. DO NOT WASH DOWN DRAIN.

WASTE DISPOSAL: SEND TO APPROVED SITE IN ACCORDANCE WITH REGULATIONS.

HANDLING PROCEDURES AND EQUIPMENT: NO SPECIAL EQUIPEMENT NEEDED. FOLLOW STANDARD PLANT HYGIENE PROCEDURE.

STORAGE REQUIREMENTS: STORE IN DRY AREAS.

SPECIAL SHIPPING INFORMATION: PROTECT AGAINST PHYSICAL DAMAGE. DOT LABEL NON-REGULATED

SECTION 8 - FIRST AID MEASURES

SPECIFIC MEASURES: GLAZE CONTAINS THE OXIDES LISTED IN THE CHEMICAL FORMULA IN FORM OF CERAMIC FRIT. SOME OF THESE OXIDES ARE ON THE INGREDIENT DISCLOSURE LIST, ONCE THESE OXIDES ARE FUSED AND CONVERTED INTO FRIT THEY ARE NO LONGER AVAILABLE IN TOXIC FORM EVEN THOUGH TESTING WOULD DETECT THE PRESENCE OF THESE OXIDES. (FRIT IS ESSENTIALLY AN INSOLUBLE SUBSTANCE). THE OXIDES ARE PRESENT IN THE FORM OF A SINTERED CERAMIC STAIN OF LOW SOLUBILITY. THESE INGREDIENTS ARE PRESENT IN A STABLE AQUEOUS SUSPENSION.

SECTION 9 - PREPARATION DATE OF MSDS

PREPARED BY
(GROUP, DEPARTMENT, ETC.)
TECHNICAL DEPT

PHONE NUMBER: (905) 695-8355

DATE
1 OCTOBER 2015